

KUT PLAST MF 100

Superplasticiser For Cement and Calcium Sulphate Based Materials

ADM-39-1110



DESCRIPTION

KUT PLAST MF 100 is a powdered super plasticizer based on a water soluble sulphonated melamine polycondensate.

APPLICATION

KUT PLAST MF 100 is especially optimized for plastification and water reduction of cement and calcium sulphate based materials.

Typical applications are:

- Self-leveling underlayments (SLU)
- Feather – edge products
- Non-shrink grouts
- Cementitious floor screeds
- Cementitious self-leveling floor screeds
- Tile adhesives and joint fillers
- Repair mortars
- Dry-mix concrete

TECHNICAL DATA

- **Form:Form:** Free flowing powder
- **Colour:** White to Off White
- **Drying loss, (%):** Max. 4.0
- **Bulk Density, (kg/m³):** 500 to 800
- **pH value 68°F, 20 % Solution:** 9.0 to 11.4
- **Dosage recommendation (%) in relation to weight of binder:** 0.20 to 2.00

PACKAGING & STORAGE

Packaging: KUT PLAST MF 100 is supplied in 20 kg bag and 500 kg jumbo bag.

Storage : Store in the original packaging (or reseal opened packages). Store in cool, dry conditions below 104° F and less than 60% relative humidity.

Shelf Life: 2 years when stored as recommended above

PRECAUTIONS

HEALTH AND SAFETY

KUT PLAST MF 100 is non-flammable.



مصنع الخصوصية لكيماويات البناء
SPECIALITIES CONSTRUCTION CHEMICALS FACTORY

Marketed by: Alghanim Specialities Co. W.L.L
Amghara Industrial Area, P.O.Box: 23595 Safat, 13096 Kuwait
Tel: 1802550 – 400 - Fax: +965 24582548 - Email: sales@spec-kw.com





ASPEC endeavours to ensure that any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

Distributor