

# KUT SILICA SAND NO IV

## Non - Slip Flooring Aggregates



MIS-22-1211

### DESCRIPTION

**KUT SILICA SAND NO IV** are chemically inert, graded, hard wearing aggregates for producing hard wearing non - skid finishes.

### USES

**KUT SILICA SAND NO IV** are highly recommended for use as non - slip aggregates for epoxy floorings and coatings when a high degree of abrasion, impact and chemical resistance is needed.

### ADVANTAGES

- Very high abrasion resistance.
- Very good chemical resistance particularly to acids, salts, oils, grease, petrochemicals etc.
- Pre - packed, ready for immediate use.

### TYPICAL PROPERTIES

- % of SiO<sub>2</sub> : 98±1%
- Bulk Density : > 1.50 kg/dm<sup>3</sup>
- Impurities : Free from organic impurities
- Nature: Quarry sand
- Hardness : 7.00 Moh's scale
- % of H<sub>2</sub>O : < 0.10 %

### SIEVE ANALYSIS

LSIEVE GRADATION

Sieve Size	% of passing
2.50 mm	100
1.25 mm	80 - 100
150 microns	0 - 30
75 microns	<10

### PACKAGING

**KUT SILICA SAND NO IV** are available in 25 kg & 50 kg. bags.

### STORAGE

Store in dry conditions in the original unopened packing.

### PRECAUTIONS

**Health & Safety:** **KUT SILICA SAND NO IV** are non hazardous .

**Fire:** **KUT SILICA SAND NO IV** are not flammable.



مصنع التخصصية لكيمائيات البناء  
**SPECIALITIES CONSTRUCTION CHEMICALS FACTORY**

Marketed by: Alghanim Specialities Co. W.L.L  
Amghara Industrial Area, P.O.Box: 23595 Safat, 13096 Kuwait  
Tel: 1802550 – 400 - Fax: +965 24582548 - Email: sales@spec-kw.com





**ASPEC** endeavours to ensure that any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

**Distributor**