

KUT SOLVENT EP

Solvent For Epoxy Systems

MIS-09-1110



DESCRIPTION

KUT SOLVENT EP is high strength solvent for various applications. **KUT SOLVENT EP** is a careful blend of selected solvents.

USES

- Clean-up of epoxy equipment and tools before Hardening. Recommended as cleaning solvent for KUT range of Epoxy Grouts and repair materials.
- Cleaner/thinner for Epoxy based solvent compatible coatings such as **KUT FLOOR COATING GP**.
- Removal of resin based curing membranes and sealers from floor surfaces.

PACKAGING

KUT SLOVENT EP is available in 5 litre packs.

PRECAUTIONS

- Do not use near open flame.
- Use only in well ventilated areas.
- Flash point is 33°C.

HEALTH AND SAFETY

KUT SOLVENT EP is flammable. Do not expose to naked flames or other sources of ignition. No smoking. Containers should be tightly sealed when not in use. In the event of fire, extinguish with CO₂ or foam.

Avoid inhalation of solvent vapours. Some people are sensitive to solvents. Gloves, goggles and barrier creams should be therefore be used. Ensure adequate ventilation, while working in closed areas, suitable breathing apparatus is recommended.



مصنع التخصصية لكيمائيات البناء
SPECIALITIES CONSTRUCTION CHEMICALS FACTORY

Marketed by: Alghanim Specialities Co. W.L.L.
Amghara Industrial Area, P.O.Box: 23595 Safat, 13096 Kuwait
Tel: 1802550 – 400 - Fax: +965 24582548 - Email: sales@spec-kw.com





ASPEC endeavours to ensure that any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

Distributor